

WATERTAP WATER FAUCET

388

IR sensor
Deck-mounted
Stainless steel with satin finish
2-year warranty



DAN DRYER WaterTap features a minimalist, modern design in stainless steel with satin finish. The water faucet is part of a complete product line, which also includes hand dryer and soap dispenser. The product line is available for either deck or wall mounting.

Technical data

Type	WATERTAP WATER FAUCET Prod. No.: 388 Touch-less water faucet with IR sensor	WATERTAP WATER FAUCET Prod. No.: 388 Touch-less water faucet with IR sensor
Dimension	H: 170 mm x Ø50/Ø38 x L: 220 mm	H: 6.69" x 1.96"/1.49"Ø x 8.66"
Material	Stainless steel, satin finish	Stainless steel, satin finish
Power connection	AC (6V)	AC (6V)
Wattage standby mode	Less than 0.1 W	Less than 0.1 W
Water pressure	10-100 PS	10-100 PS
Water temperature	4-85° C	39.2-185 F
Activation time	0.5-1 sec	0.5-1 sec
Flow rate	Less than 3.8 l/min.	Less than 3.8 l/min.
Net weight	1.7 kg	3.74 lb
IP rating	IP35	IP35
Tender text	Touch-less water tap in stainless steel with satin finish for table top mounting. Infra-red sensor and electronic timer, power connection AC (6V), IP35, water pressure 10-100 PSI, water temperature 4-85°C, activation 0.5-1 sec., flow rate < 3.8 l/min. Net weight: 1.7 kg	Touch-less water tap in stainless steel with satin finish for table top mounting. Infra-red sensor and electronic timer, power connection AC (6V), IP35, water pressure 10-100 PSI, water temperature 4-85°C, activation 0.5-1 sec., flow rate < 3.8 l/min. Net weight: 3.74 lb

Application

DAN DRYER WaterTap with automatic sensor for touch-less activation is a hygienic solution for commercial washrooms. It is easy to operate and simple to manage by all kinds of users, including children and people with reduced hand mobility. The DAN DRYER Tap range is an ideal build-in solution for construction projects and automatic hand wash stations.

References

Shopping centres, restaurants, hotels, airports, sports facilities, schools and public institutions.

Standard colour

Stainless steel, satin finish.

Activation

Infrared sensor and electronic timer. Touchfree. Activation distance adjustable between 20 - 120 mm / 0.78" - 4.72".

Installation

Machine intended for wall mounting. Connection to fixed installation or via circuitbreaker. Installation must be carried out by a qualified electrician.

Approval

